

LR-2000 INSTALLATION KIT & ACCESSORIES

The LR-2000KIT is the mandatory test & setup Kit required to successfully install the AWID LR-2000 parking access reader. All install kits include the following in its own ruggedized carrying case:



- Customized LR-2000 test unit with mounting straps, allows set up and testing in various placements to determine best read range and vehicle approach
- SP-6820-LR test unit with LED, beeper and cable, allows visual and audible indicator of successful tag reads when setting up and testing
- PS-12-3.3A power supply, 12V 3.3A
- CS-UHF-0-0 UHF Clamshell Badge
- GR-UHF-0-0 UHF Graphics Quality Badge
- VT-UHF-0-0 UHF Visor Tag
- HT-UHF-0-0 UHF Hang Tag
- RV-UHF-0-0 UHF Rear View Mirror Tag
- WS-UHF-0-0 UHF Windshield Tag
- UHF Detector. Detects frequencies from 50 MHz to 3GHz

The LR-2000 Installation Kit must be used for all installations of the LR-2000 reader and tags.



LR-911MB

The LR-911MB Mounting Bracket is specifically chosen for use with the LR series readers including the LR-2000. The LR-911MB has an adjustable head which facilitates the aiming of the LR readers via flexible up/down and side/side movement. The LR-911MB can be mounted in either a vertical or horizontal position allowing for maximum flexibility



PS-12-3.3A

The PS-1233A has output of 12 volts DC, 3 ampere capacity, which is suitable for powering the LR-2000 reader.